

Majestic Polymeric 3



Polymeric 3 is a very high durability polymer that is specially designed to provide a semi-permanent coating that can be used on concrete, marble, terrazzo and other stone floors. It is formulated to provide a more durable floor coating than most conventional seals and finishes. It can also be used in outdoor applications.

For Use On: All concrete, natural stone and resilient floors such as vinyl and linoleum.

Available Sizes: Gallon, case of 4 gallons, 5 gallon, 55 gallon

Coverage: Depending on the porosity of the floor surface, coverage will be between 800-1,200 sq. ft. per gallon.

Product Features:

- Creates a durable high gloss finish capable of withstanding heavy traffic
- Creates a water and chemical-resistant finish
- Can be used in outdoor applications

THOROUGHLY TESTED

Directions:

Clear the area of all movable objects. Sweep the floor clean of loose dirt and rubbish. If the floor surface has previously been coated with a floor finish, it must be stripped and remove all old wax and floor finish. Care should be taken in insure that the unfinished surface is very clean and dry.

1. Rinse the floor as thoroughly as possible and let dry.
2. Work with clean equipment and apply a thin coat of product.
3. Allow to dry completely (a minimum of 2 hours) before applying another coat. Apply 1 to 2 coats allowing plenty of time between coats for drying. Do not resume traffic on the surface for at least 12 hours. Light foot traffic before that is fine, but no heavy cart or vehicle traffic.
4. Sweep daily with dust mop/cloth. Clean with neutral pH cleaner. Light cleaning will remove surface soils, stains and maintain gloss and color. Dry buff or burnish after cleaning to obtain a glossy look. Heavy traffic lanes may need to be maintained with a spray buff or restorer.

M3 Technologies, Inc.
57 Lamberts Lane
Cohasset, MA 02025
Toll Free: 800-342-4533
Fax: 781-383-3135
www.m3techinc.com

