

# Majestic Stone Soap



Stone Soap is an all natural, biodegradable, highly concentrated cleaner/conditioner designed for daily cleaning and conditioning of all natural stone surfaces. Stone Soap is safe and easy to use on marble, granite, limestone, travertine, terrazzo, agglomerate, slate, unglazed ceramic, porcelain, terra cotta, saltillo and concrete. Regular use provides a dirt repellent barrier at the surface, prevents hard water damage, brings out the natural color and brilliance of the stone, and improves slip resistance on polished surfaces.

**For Use On:** All natural stone surfaces

**Available Sizes:** Gallon, case of 4 gallons, 5 gallon, 55 gallon

**Coverage:** 20,000 - 40,000 sq. ft./gallon, depending on dilution.

**Product Features:**

- Interior and exterior
- No-rinse, biodegradable
- Easy-to-use natural protection

## THOROUGHLY TESTED

**Directions:**

**For Damp Mopping** - Dilute Stone Soap at a dilution rate of 1 oz. per gallon with clean water for light traffic areas, 2-3 ounces per gallon for moderate to heavy traffic areas. Soak and wring mop and apply solution to the stone surface. Do not rinse or re-mop. Re-wet and wring mop often to avoid re-depositing dirt to the surface. Change the solution when it appears dirty. Best results will be achieved when buffed on polished surfaces. Using white polishing pad with any speed equipment, always buff after initial application of Stone Soap, then buff floor after every 4th application, depending upon traffic and surface appearance. NOTE: Best results are achieved when cotton mops are not used. Rayon blend mops are recommended on polished surfaces.

**For Automatic Scrubbers** - Dilute Stone Soap at the rate of 1 ounce per gallon. Adjust flow rate valve so that the solution wets the surface but does not flood surface. Pass the scrubber over the floor in a manner that does not re-apply the solution onto previously scrubbed areas. Drop but do not lock the vacuum squeegee and turn vacuum on. Use red or white buffing pad.

M3 Technologies, Inc.  
 57 Lamberts Lane  
 Cohasset, MA 02025  
 Toll Free: 800-342-4533  
 Fax: 781-383-3135  
 www.m3techinc.com

