

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/05/2020

Reviewed on 11/05/2020

## 1 Identification

· **Product identifier**

· Trade name: **Majestic Color Enhancing Sealer**

· Article number:

· Application of the substance / the mixture

Sealing

· **Details of the supplier of the safety data sheet**

· Manufacturer/Supplier: InnoChem LLC  
6300 Button Gwinnett Dr.  
Atlanta, GA 3040  
info@innocemllc.com

Phone: 770-409-8789

Fax: 770-409-9096

e-mail

· Information department:

Laboratory

· Emergency telephone number:

Refer to Manufacturer / Supplier

## 2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **Label elements**

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word

Danger

· Hazard-determining components of labeling:

· Hazard statements

Distillates (petroleum), hydro- treated light

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261

Avoid breathing vapours.

P280

Wear protective gloves.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P331

Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312

Call a poison center/doctor if you feel unwell.

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/05/2020

Reviewed on 11/05/2020

**Trade name: Majestic Color Enhancing Sealer**

(Contd. of page 1)

P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:**  
 - NFPA ratings (scale 0 - 4)


Health = 1  
 Fire = 2  
 Reactivity = 0

 - HMS-ratings (scale 0 - 4)


Health = 1  
 Fire = 2  
 Reactivity = 0

**Other hazards**

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

**3 Composition/information on ingredients**
**Chemical characterization: Mixtures**

- Description: Mixture of the substances listed below with nonhazardous additions.

 - Dangerous components:

64742-47-8	Distillates (petroleum), hydro- treated light Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	50-100%
68553-15-1	Linseed oil, cobalt manganese salt (Linseed oil, manganese and cobalt driers) Skin Irrit. 2, H315; Eye Irrit. 2A, H319	1-5%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

**4 First-aid measures**
**Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. Take affected persons out into the fresh air. Position and transport stably on side.
- After inhalation: Supply fresh air; consult doctor in case of complaints. In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help. Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor: Symptoms in intoxication with (aromatic) hydrocarbons (dosis letalis about 30 g)
  - a) In acute intoxication: headache, dizziness, euphoria, gastro-intestinal dysfunction, state of excitement, coma.
  - b) In chronic intoxication: myelotoxic damage, fatigue, dizziness, emaciation, cardiac palpitation after physical exercise, leucopenia, anemia, leukosis.
 Therapy in hydrocarbons intoxication: In case of inhalation provision of fresh air; in case of peroral intake administration of Carbo medicinalis; only after intubation conduct of gastrolavage in application of Carbo medicinalis; in case of cramps administration of Diazepam 20 mg intravenously.
- Most important symptoms and effects, both acute and delayed Headache

(Contd. on page 3)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/05/2020

Reviewed on 11/05/2020

**Trade name: Majestic Color Enhancing Sealer**

(Contd. of page 2)

- Danger
  - Indication of any immediate medical attention and special treatment needed
- Dizziness  
Nausea  
Coughing  
Profuse sweating  
Danger of impaired breathing.

If swallowed, gastric irrigation with added, activated carbon.  
If swallowed or in case of vomiting, danger of entering the lungs.

**5 Fire-fighting measures**

- **Extinguishing media**

- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents:

Water with full jet

- **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.  
In case of fire, the following can be released:  
Carbon monoxide (CO)  
In certain fire conditions, traces of other toxic gases cannot be excluded.

- **Advice for firefighters**

- Protective equipment:

Wear fully protective suit.  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.

- **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Keep away from ignition sources

- **Environmental precautions:**

Use respiratory protective device against the effects of fumes/dust/aerosol.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow product to reach sewage system or any water course.  
Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- PAC-1:

None of the ingredients is listed.

- PAC-2:

None of the ingredients is listed.

(Contd. on page 4)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/05/2020

Reviewed on 11/05/2020

**Trade name: Majestic Color Enhancing Sealer**

(Contd. of page 3)

**PAC-3:**

None of the ingredients is listed.

**7 Handling and storage**
**Handling:**

- Precautions for safe handling      Ensure good ventilation/exhaustion at the workplace.  
Keep receptacles tightly sealed.  
Store in cool, dry place in tightly closed receptacles.  
Keep away from heat and direct sunlight.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
Use only in well ventilated areas.

- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Protect from heat.

- **Conditions for safe storage, including any incompatibilities**

- Storage:

- Requirements to be met by storerooms and receptacles:

Store in a cool location.  
Store only in the original receptacle.  
Prevent any seepage into the ground.

- Information about storage in one common storage facility:

Store away from oxidizing agents.  
Store away from foodstuffs.

- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.  
Keep receptacle tightly sealed.  
Protect from heat and direct sunlight.  
Store receptacle in a well ventilated area.  
Store in a cool place.

- Storage class:

3

- **Specific end use(s)**

No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:**

No further data; see item 7.

- **Control parameters**

- Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

**64742-47-8 Distillates (petroleum), hydro- treated light**
TLV | Long-term value: 200 mg/m<sup>3</sup>

- Additional information:

The lists that were valid during the creation were used as basis.

- **Exposure controls**

- Personal protective equipment:

- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

(Contd. on page 5)

US

# Safety Data Sheet


## acc. to OSHA HCS

Printing date 11/05/2020

Reviewed on 11/05/2020

### Trade name: Majestic Color Enhancing Sealer

(Contd. of page 4)

- Do not inhale gases / fumes / aerosols.  
Do not eat, drink, smoke or sniff while working.  
Apply solvent resistant skin cream before beginning work.  
Use skin protection cream for skin protection.
- Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.  
Use suitable respiratory protective device in case of insufficient ventilation.  
Filter AX
- Protection of hands: Preventive skin protection by use of skin-protecting agents is recommended.  
After use of gloves apply skin-cleaning agents and skin cosmetics.  
Skin protection agent recommendation for preventive skin shelter without use of protective gloves  
Stokoderm Protect PURE (<http://www.debstoko.com>)  
Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:  
Stokoderm Protect PURE (<http://www.debstoko.com>)  
Skin protection recommendation for skin cleaning after product handling:  
Estesol Lotion PURE (<http://www.debstoko.com>)  
Skin protection agent recommendation for skin aftercare:  
Stokolan Light PURE (<http://www.debstoko.com>)  
The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.  
This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).
-  Protective gloves
- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves Fluorocarbon rubber (Viton)  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.  
Value for the permeation: Level ≤ 6, 480 min
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)  
Vitoject (KCL, Art\_No. 890)
- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR  
Camatril (KCL, Art\_No. 730, 731, 732, 733)  
Fluorocarbon rubber (Viton)  
Vitoject (KCL, Art\_No. 890)
- Not suitable are gloves made of the following materials: Rubber gloves  
Natural rubber, NR

(Contd. on page 6)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 11/05/2020

Reviewed on 11/05/2020

**Trade name: Majestic Color Enhancing Sealer**

(Contd. of page 5)

- |                           |                          |
|---------------------------|--------------------------|
|                           | Butyl rubber, BR         |
| · <u>Eye protection:</u>  | Leather gloves           |
| · <u>Body protection:</u> | Safety glasses           |
|                           | Protective work clothing |

**9 Physical and chemical properties**
**· Information on basic physical and chemical properties**
**· General Information**
**· Appearance:**

- |                 |               |
|-----------------|---------------|
| · <u>Form:</u>  | Fluid         |
| · <u>Color:</u> | Yellowish     |
| · <u>Odor:</u>  | Specific type |

- |                    |                |
|--------------------|----------------|
| · <u>pH-value:</u> | Not applicable |
|--------------------|----------------|

**· Change in condition**

- |                                       |                             |
|---------------------------------------|-----------------------------|
| · <u>Melting point/Melting range:</u> | Undetermined.               |
| · <u>Boiling point/Boiling range:</u> | 158.9-178.9 °C (318-354 °F) |

- |                       |                         |
|-----------------------|-------------------------|
| · <u>Flash point:</u> | 40-41 °C (104-105.8 °F) |
|-----------------------|-------------------------|

- |                         |                              |
|-------------------------|------------------------------|
| · <u>Auto igniting:</u> | Product is not selfigniting. |
|-------------------------|------------------------------|

- |                               |  |
|-------------------------------|--|
| · <u>Danger of explosion:</u> | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
|-------------------------------|--|

**· Explosion limits:**

- |                 |           |
|-----------------|-----------|
| · <u>Lower:</u> | 0.8 Vol % |
| · <u>Upper:</u> | 7 Vol %   |

- |                          |                 |
|--------------------------|-----------------|
| · <u>Vapor pressure:</u> | Not determined. |
|--------------------------|-----------------|

- |                                    |                                       |
|------------------------------------|---------------------------------------|
| · <u>Density at 20 °C (68 °F):</u> | 0.78 g/cm <sup>3</sup> (6.51 lbs/gal) |
|------------------------------------|---------------------------------------|

- |   |                                       |
|---|---------------------------------------|
| · <u>Specific gravity at 20 °C (68 °F):</u> | 0.89 g/cm <sup>3</sup> (7.43 lbs/gal) |
|---|---------------------------------------|

**· Solubility in / Miscibility with**

- |                 |                                   |
|-----------------|-----------------------------------|
| · <u>Water:</u> | Not miscible or difficult to mix. |
|-----------------|-----------------------------------|

- |   |                 |
|---|-----------------|
| · <u>Partition coefficient (n-octanol/water):</u> | Not determined. |
|---|-----------------|

**· Viscosity:**

- |                     |                 |
|---------------------|-----------------|
| · <u>Dynamic:</u>   | Not determined. |
| · <u>Kinematic:</u> | Not determined. |

**· Solvent content:**

- |                            |        |
|----------------------------|--------|
| · <u>Organic solvents:</u> | 97.5 % |
|----------------------------|--------|

- |                          |       |
|--------------------------|-------|
| · <u>Solids content:</u> | 0.0 % |
|--------------------------|-------|

**· Other information**

No further relevant information available.

**10 Stability and reactivity**
**· Reactivity**

No further relevant information available.

**· Chemical stability**
**· Thermal decomposition / conditions to be avoided:**

No decomposition if used and stored according to specifications.  
 No decomposition if used according to specifications.

**· Possibility of hazardous reactions**

Reacts with strong oxidizing agents.

**· Conditions to avoid**

No further relevant information available.

**· Incompatible materials:**

No further relevant information available.

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/05/2020

Reviewed on 11/05/2020

**Trade name: Majestic Color Enhancing Sealer**

(Contd. of page 6)

- **Hazardous decomposition products:** No dangerous decomposition products known.

## \* 11 Toxicological information

### · **Information on toxicological effects**

- Acute toxicity:
- Primary irritant effect:
  - on the skin: Irritant to skin and mucous membranes.
  - on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information: Harmful  
Irritant  
The product shows the following dangers according to internally approved calculation methods for preparations:

### · Carcinogenic categories

#### · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

#### · NTP (National Toxicology Program)

None of the ingredients is listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## \* 12 Ecological information

### · **Toxicity**

- Aquatic toxicity: No further relevant information available.
- **Persistence and degradability** No further relevant information available.

### · **Behavior in environmental systems:**

- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.

### · **Ecotoxicological effects:**

- Remark: Toxic for fish

### · **Additional ecological information:**

- General notes: Do not allow product to reach ground water, water course or sewage system.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms  
Water hazard class 1 (Self-assessment): slightly hazardous for water

### · **Results of PBT and vPvB assessment**

- PBT: Not applicable.
- vPvB: Not applicable.
- **Other adverse effects** No further relevant information available.

## \* 13 Disposal considerations

### · **Waste treatment methods**

- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

### · **Uncleaned packagings:**

- Recommendation: Disposal must be made according to official regulations.  
Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

- Recommended cleansing agent: Alcohol

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/05/2020

Reviewed on 11/05/2020

**Trade name:** Majestic Color Enhancing Sealer

(Contd. of page 7)

**14 Transport information**· **UN-Number**· DOT, ADR, IMDG, IATA UN1263· **UN proper shipping name**

· DOT Paint related material  
 · ADR 1263 PAINT RELATED MATERIAL  
 · IMDG, IATA PAINT RELATED MATERIAL

· **Transport hazard class(es)**· DOT

· Class 3 Flammable liquids  
 · Label 3

· ADR

· Class 3 (F1) Flammable liquids  
 · Label 3

· IMDG, IATA

· Class 3 Flammable liquids  
 · Label 3

· **Packing group**· DOT, ADR, IMDG, IATA III· **Environmental hazards:**

Not applicable.

· **Special precautions for user**

Warning: Flammable liquids

· Hazard identification number (Kemler code): 30· EMS Number: F-E,S-E· Stowage Category A· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**· DOT

· Quantity limitations On passenger aircraft/rail: 60 L  
 On cargo aircraft only: 220 L

· ADR

· Excepted quantities (EQ) Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)

US



# Safety Data Sheet

acc. to OSHA HCS

Printing date 11/05/2020

Reviewed on 11/05/2020

**Trade name: Majestic Color Enhancing Sealer**

(Contd. of page 8)

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>· <u>IMDG</u></li> <li>· <u>Limited quantities (LQ)</u></li> <li>· <u>Excepted quantities (EQ)</u></li> </ul> | <p>5L<br/>Code: E1<br/>Maximum net quantity per inner packaging: 30 ml<br/>Maximum net quantity per outer packaging: 1000 ml</p> |
| <ul style="list-style-type: none"> <li>· <b><u>UN "Model Regulation":</u></b></li> </ul>   | <p>UN 1263 PAINT RELATED MATERIAL, 3, III</p>  |

**15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Sara

- Section 355 (extremely hazardous substances):

None of the ingredient is listed.

- Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- TSCA (Toxic Substances Control Act):

68553-15-1	Linseed oil, cobalt manganese salt (Linseed oil, manganese and cobalt driers)	ACTIVE
------------	--	--------

- Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65

- Chemicals known to cause cancer:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Carcinogenicity categories

- EPA (Environmental Protection Agency)

None of the ingredients is listed.

- TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

- MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

- NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- GHS label elements

- Hazard pictograms

The product is classified and labeled according to the Globally Harmonized System (GHS)



GHS02 GHS07 GHS08

- Signal word

Danger

- Hazard-determining components of labeling:

Distillates (petroleum), hydro- treated light  
H226 Flammable liquid and vapor.  
H315 Causes skin irritation.

- Hazard statements

(Contd. on page 10)<sup>US</sup>

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 11/05/2020

Reviewed on 11/05/2020

**Trade name: Majestic Color Enhancing Sealer**

(Contd. of page 9)

- Precautionary statements
  - H336 May cause drowsiness or dizziness.
  - H304 May be fatal if swallowed and enters airways.
  - P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
  - P261 Avoid breathing vapours.
  - P280 Wear protective gloves.
  - P301+P310 If swallowed: Immediately call a poison center/doctor.
  - P331 Do NOT induce vomiting.
  - P302+P352 If on skin: Wash with plenty of water.
  - P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
  - P312 Call a poison center/doctor if you feel unwell.
  - P403+P233 Store in a well-ventilated place. Keep container tightly closed.
  - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
  
- National regulations:
  
- Information about limitation of use: Employment restrictions concerning young persons must be observed.  
Employment restrictions concerning pregnant and lactating women must be observed.
  
- Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
  
- VOC USA 760.5 g/l / 6.35 lb/gal
  
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Laboratory
- Date of preparation / last revision 11/05/2020 / -
- Abbreviations and acronyms:
  - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
  - ICAO: International Civil Aviation Organisation
  - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - DOT: US Department of Transportation
  - IATA: International Air Transport Association
  - ACGIH: American Conference of Governmental Industrial Hygienists
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - NFPA: National Fire Protection Association (USA)
  - HMS: Hazardous Materials Identification System (USA)
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - NIOSH: National Institute for Occupational Safety
  - OSHA: Occupational Safety & Health
  - TLV: Threshold Limit Value
  - PEL: Permissible Exposure Limit
  - REL: Recommended Exposure Limit
  - Flam. Liq. 3: Flammable liquids – Category 3
  - Skin Irrit. 2: Skin corrosion/irritation – Category 2
  - Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
  - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
  - Asp. Tox. 1: Aspiration hazard – Category 1